



SPECIFICATIONS:

1. CONTACT RESISTANCE: 20m OHM.
2. INSULATION RESISTANCE: DC 500V 100M OHM MIN.
3. VOLTAGE WITHSTANDING: AC 500V 1 MINUTE.
4. INSERTION FORCE: 4KG MAX.
5. WITHDRAWAL FORCE: 1-3.5 KG.
6. LIFE TEST: 5000 CYCLES MIN. AFTER TESTING, CONTACT RESISTANCE SHALL NOT EXCEED 100m OHM.
7. CURRENT RATING: AC: 100V 2A.
DC: 24V 1A

4.	CONTACT TERMINAL	7	BSR-H/20.7t	Pb10%,Sn90%	
3.	EARTH TERMINAL	1	PBSR 0.25t	Pb10%,Sn90%	
2.	COVER	1	P.B.T.	DR-48	UL94V-0
1.	BODY	1	P.B.T.	DR-48	UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

DJ-SQ-07-LF

SERIES | LEADFREE
| 07 WAY
| SQUARE
| ALL PLASTIC

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: