



SPECIFICATION:
ELECTRICAL
 1. RATING: 100V AC 2A
 2. CONTACT RESISTANCE: 20m OHM MAX.
 3. INSULATION RESISTANCE: 300M OHM MIN. AT DC 500V
 4. VOLTAGE WITHSTANDING: AC 1000V FOR ONE MINUTE
MECHANICAL
 1. INSERTION FORCE: 6.5KGS MAX.
 2. WITHDRAWAL FORCE: 1-5KGS

ARRANGEMENT OF CONTACTS				
	MODEL NO.	DJD-F-04	DJD-F-06	DJD-F-07
HOLE LAYOUT				

5.	RIVET	1	AL	NICKEL PLATED	
4.	CONTACT TERMINAL	8	BRASS 0.7t	Pb10%, Sn90%	
3.	EARTH TERMINAL	1	PBSR-H 0.25t	Pb10%, Sn90%	
2.	INSULATOR	1	P.B.T.	VALOX 420-SEO	UL94V-0
1.	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

DJD-F-xx-LF
 LEADFREE
 RoHS Compliant



PART NO. DJD-F-xx	
DWG NO. DJD-F-xx	
FILE NO.	CHECKED BY CY
UNIT / mm	DRAWING BY
SCALE 1:1	PROJECTION

TOLERANCES ARE
.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:	
AREA	REVISIONS
HK	DATE

煜倫股份有限公司