



PCB LAYOUT  
(TOP VIEW)

DJD-M-xx-LF  
LEADFREE  
RoHS Compliant

5. SPECIFICATION:  
**ELECTRICAL**

1. RATING: 100V AC 2A
2. CONTACT RESISTANCE: 20m OHM MAX.
3. INSULATION RESISTANCE: 300M OHM MIN. AT DC 500V
4. VOLTAGE WITHSTANDING: AC 1000V FOR ONE MINUTE

**MECHANICAL**

1. INSERTION FORCE: 6.5KGS MAX.
2. WITHDRAWAL FORCE: 1.5KGS

ARRANGEMENT OF CONTACTS				
MODEL NO.	DJD-M-04	DJD-M-06	DJD-M-07	DJD-M-08
HOLE LAYOUT				

5.	RIVET	1	AL	NICKEL PLATED	
4.	CONTACT TERMINAL	4-8	BRASS 0.7t	Pb10%, Sn90%	
3.	EARTH TERMINAL	1	PBSR-H 0.25t	Pb10%, Sn90%	
2.	INSULATOR	1	P.B.T.		UL94V-0
1.	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

**MORE THAN ALL**  
CONNECTORS  
ASSEMBLIES

PART NO. DJD-M-xx

DWG NO. DJD-M-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司