



ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 100V AC AT 1AMP MAX OR
12V DC AT 2AMPS MAX

Insulation Resistace 50 Megohms Minimum at DC 250V
Dielectric Strength: 250V AC/1 MIMUTE

MECHANICAL CHARACTERISTICS:

Contact Insertion Force: 4.5Kg Maximum
Contact Separation Force: 0.9Kg Mimlrum

MATERIALS:

Contacts: Brass
Insuslator, PBT, UL 94V-0 Rated
Shell: Brass

FINISHES:

Contact: Nickel Plated.
Shell: Nickel Plated.

HOUSING MATERIAL

- 1: LCP (WHITE)
- 2: LCP (BLACK)
- 3: NYLON 6T (WHITE)
- 4: NYLON 6T (BLACK)
- 5: PBT (WHITE)
- 6: PBT (BLACK)

SHELL MATERIAL

- 1: SPCC
- 2: BRASS

TERMINAL CONTACT PLATING

- 1: Sn 120U''
- 2: Ni 120U''

TERMINAL MATERIAL

- 1: PHOSPHOR BRONZR
- 2: BRASS

NO.	PART NAME	MATERIAL	FINISH	Q'TY
4	弹片	磷铜 t=0.20	镀 Sn 120U''	1
3	铜管	黄铜 t=0.40	镀 Ni 120U''	1
2	端子	黄铜 t=0.60	镀 Sn 120U''	5
1	胶芯	PBT+30%,UL94V0	BLACK	1

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

- X. ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

PPOJECTION

照片框

ORDER INFORMATION

DM-SE-05-LF
SERIES | LEADFREE
05 WAY
EARTH WIRE
FEMALE

DESCRIPTION: