



Material: Post: Brass, Tin/Plated
 Base: Nylon 66, UL94V-2
 Qty: 500 pcs/bag

SPECIFICATIONS

Accepts cantilever crimp terminal
 Housing Nylon 66 (UL94V-2)
 Mates with 0.084" (2.13mm) crimp terminal housing
 Terminal Retention to housing—8lbs (3.63kg) min.
 Voltage: rating: AC, DC, 250V
 Current rating: 7A, AC, DC
 Withstand voltage: 1500V AC/minute
 Insulation resistance: 1000M Ω min
 Temperature range: -25°C~+90°C
 Contact resistance: Initial Valueable/10m Ω max.
 After environmental testing/20m Ω max.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, \pm
 .X \pm 0.30
 .XX \pm 0.20
 .XXX \pm 0.10
 ANG \pm 2°

照片框

ORDER INFORMATION

DP-PDS-04-LF
 SERIES | LEADFREE
 | 04WAY
 RIB
 DIP 180°
 MALE

DESCRIPTION: PITCH 5.08 DISK DRIVER POWER CONNECTOR SYSTEM