



A	COLOR	B	C
1	YELLOW	1	
	YELLOW		1
2	BLACK	2	
	BLACK		2
3	BLACK	3	
	BLACK		3
4	RED	4	
	RED		4

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #22 YELLOW	2PCS	E108485
2	WIRE:	UL1007 #22 BLACK	1PCS	E108485
3	WIRE:	UL1007 #22 RED	1PCS	E108485
4	HOUSING:	DP-P-04	1PCS	E144544
5	TERMINAL:	DP-M-18	4PCS	E144544
6	HOUSING:	EI-H-04	2PCS	E144544
7	TERMINAL:	EI-T-22	8PCS	E144544
8				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

DPEIX12-040422-E9N-LF

SERIES

LEADFREE
230mm
MALE TO FEMALE
22 AWG
04 TO 04 WAY

DESCRIPTION: