



A	COLOR	B	C
1	YELLOW	1	
	YELLOW		4
2	BLACK	2	
	BLACK		3
3	BLACK	3	
	BLACK		2
4	RED	4	
	RED		1

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #22 YELLOW	1PCS	E108485
2	WIRE:	UL1007 #22 BLACK	2PCS	E108485
3	WIRE:	UL1007 #22 RED	1PCS	E108485
4	WIRE:	UL1007 #22 YELLOW	1PCS	E108485
5	WIRE:	UL1007 #22 BLACK	2PCS	E108485
6	WIRE:	UL1007 #22 RED	1PCS	E108485
7	HOUSING:	DP-P-04	1PCS	E149293
8	TERMINAL:	DP-M-22	4PCS	
9	HOUSING:	DP-S-04	1PCS	E149293
10	TERMINAL:	DP-F-22	4PCS	
11	HOUSING:	EI-H-04	1PCS	E149293
12	TERMINAL:	EI-T-22	4PCS	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

DPEIX3-044422-E15C-LF

SERIES

LEADFREE
150mm
MALE TO FEMALE
22 AWG
04.04.04 WAY

DESCRIPTION: CABLE ASS"Y