



ELECTRICAL PROPERTIES

- 1.100% OPEN SHORT MIS-WIRE TEST
- 2.CONTACT RESISTANCE 5 OHM MAX
- 3.INSULATION RESISTANCE 20 MEGA OHM MIN
- 4.HIPOT TEST DC 300V 10MS

| P1 | COLOR  | P2       |
|----|--------|----------|
| 1  | YELLOW | 1+2+3    |
| 2  | BLACK  | 4+5+6    |
| 3  | BLACK  | 10+11+12 |
| 4  | RED    | 7+8+9    |

|     |   |      |       |
|-----|---|------|-------|
| 6   | TER: 4P(M)(ROHS)                                    | 4    | PC    |
| 5   | HSG: 4PIN"(F) PH: 5.08MM COLOR: WHITE               | 1    | PC    |
| 4   | SERIAL ATA CONNECTOR STRAIGHT 15P/F<br>COLOR: BLACK | 1    | PC    |
| 3   | UL1007 #18 TS COLOR: RED.                           | 1    | PC    |
| 2   | UL1007 #18 TS COLOR: BLACK.                         | 2    | PC    |
| 1   | UL1007 #18 TS COLOR: YELLOW.                        | 1    | PC    |
| NO. | DESCRIPTION   | Q'TY | UNITS |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PJECTION

照片框

ORDER INFORMATION

DPSA-041518-E25C-LF

SERIES

LEADFREE

250mm

MALE TO FEMALE

18 AWG

04 TO 15 WAY

DESCRIPTION: