



PIN ASSIGNMENT

- | | | |
|----|------------|----------|
| P1 | | P2 |
| 1 | — YELLOW — | 1+2+3 |
| 2 | — BLACK — | 4+5+6 |
| 4 | — RED — | 7+8+9 |
| 3 | — BLACK — | 10+11+12 |

*	390	CARTON: 46*30*15CM	1/500	PCS
*	390	PE BAG: 30*28*0.08MM	1/500	PCS
*	390	PE BAG: 6*8*0.06MM	1/10	PCS
9	230	HOUSING: YY-3200-H-04PIN<WHξ??>	1	PCS
8	230	TERMINAL: YY-3200-T<TIN>(??)(??)	4	PCS
7	370	PP?/BK	7.0	G
6	370	PVC-IN	0.5	G
5	220	SOL-WIRE-63/37-1.0	0.2	G
4	220	SERIAL ATA:15S/BK	1	PCS
3	220	JUMP WIRE-18-RED-4.5*130*2MM-2.1U1007	1	PCS
2	220	JUMP WIRE-18-BLACK-4.5*130*2MM-2.1U1007	2	PCS
1	220	JUMP WIRE-18-YELLOW-4.5*130*2MM-2.1U1007	1	PCS
NO	PART NO.	DESCRIPTION	QTY	UNIT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

DPSA-041518-E6N-LF

SERIES

LEADFREE

150mm

MALE TO FEMALE

18 AWG

04 TO 15 WAY

DESCRIPTION: SATA POWER CABLE L:150mm