



P1	P2	SYMBOL	WIRE COLOR
1			
2	---	---	---
3			
4			
5	3	GND	BLACK
6			
7			
8	4	V5	RED
9			
10			
11	2	GND	BLACK
12			
13			
14	1	V12	YELLOW
15			

WIRING TABLE

ITEM	DESCRIPTION	Q'TY
6	ID LABEL, 40mm x 60mm, FOR CARTON, WHITE (SHEET 2 OF 2)	1 PC
5	ID LABEL, 24mm x 43mm, FOR PE BAG, WHITE (SHEET 2 OF 2)	1 PC
4	POWER CONN ., SOCKET CONTACT , UL 94V- 2	4 PCS
3	POWER CONN ., HOUSING, 4-POS., 5.08mm PITCH, TRAN SPARENT WHITE, UL 94V-2	1 PC
2	SERIAL ATA CONN., 15-POS., POWER FOR CABLE, IDC TYPE, W/CABLE STOP , UL 94V-0	PCS
1	WIRE, 18 AWG , UL 1007, VW -1 (Per Rei Hsing Specification)	A/R

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

DPSA-0415R18-E50C-LF

SERIES

LEADFREE

500mm

MALE TO FEMALE

18 AWG

04P TO 15P 90°

DESCRIPTION: