



- Note:
- Material:
 - Insulator: High temperature thermoplastic with g.f,UL94v-0
 - Contact: Copper alloy,t=0.20mm
 - Shell: Spcc,t=0.30mm
 - Specification:
 - Current rating: 1 A Max.
 - Dielectric withstanding voltage: 750 V(ac) for 1 min.
 - Contact resistance: 30 mΩ Max.
 - Insulation resistance: 1000 MΩ Min.
 - Total mating force: 7.0 Kgf Max.
 - Total unmating force: 1.5 Kgf Min.
 - Temperature range: -55°C~85°C

8	Back-shell			
7	Front-shell			
6	Clip			No finish
5	Contact			Selective Au plated on mating area
4	Contact			
3	Contact			
2	Contact			
1	Housing			Black
No.	Name	Q'ty	Part No.	Finish

PART NO.	A±0.25	B±0.2	C±0.2	D±0.2	E±0.2	I±0.1
DR-PS-09	30.81	24.99	16.92	8.38	12.55	2.84
DR-PS-15	39.25	33.32	25.25	8.38	12.55	2.84
DR-PS-25	53.04	47.04	38.96	8.38	12.55	2.84
DR-PS-37	69.32	63.50	55.42	8.38	12.55	2.84

DR-PS-xx-LF
LEADFREE
RoHS Compliant

	PART NO. DR-PS-xx		CHECKED BY CY	TOLERANCES ARE X. ± .X ± 0.3 .XX ± 0.20 .XXX ± ANG ±1'	DESCRIPTION: D-SUB RIGHT ANGLE P. B. C TYPE (M)		
	DWG NO. DR-PS-xx				DRAWING BY	AREA	REVISIONS
	FILE NO.		PROJECTION				
	UNIT / mm	SCALE 1:1					