



Electrical Characteristics:

1. Current Rating: 5 AMP
2. Withstanding Voltage: AC 500V for 1 Minute.
3. Insulation Resistance: 1000MΩ Min. at DC 500v.
4. Contact Resistance: 15mΩ Max.
5. Operating Temperature: -40° c to 105° c.

Material:

1. Insulator: PBT+30% Glass Fiber (UL94v-0).
 2. Contact: Brass
 3. Contact plated: Glod Flash over Tin or Glod Plated Tin Plated
 4. Shell: Steel Nickel Plated
 5. Housing color: Black
- Plus "*" as the key control size

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ± 0.15
ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

DR-PSNJ-09-LF
SERIES | | | | LEADFREE
| | | | 09 WAY
| | | | JACKSCREW
| | | | NUT
| | | | SEMI GOLD
| | | | MALE

DESCRIPTION: DR9 公叉鉚鎖半金 8.1

煜倫股份有限公司

www.morethanall.com