

NOTES: P.C.B. LAYOUT

1.MATERIAL

- 1.1 Insulator:PBT+30%Glass Fiber (UL94V-0)
- 1.2 Contact:Brass
- 1.3 Contact Plated:Gold/TIN PLATED
- 1.4 Shell:Steel,Nickel Plated
- 1.5 Screw:Brass, Nickel Plated

2.SPECIFICATION

- 2.1 Current Rate:5 Amps
- 2.2 Insulator Resistance:5000MΩ Min. at 500V DC
- 2.3 Dielectric Strength:1000V Per minute
- 2.4 Operation Temperature:-55°C to+105°C

DR-PxNGR-09-LF
LEADFREE
GR:GREEN/COLOR
S:SEMI/GOLD
G:FULL/GOLD

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. DR-PxNGR-09

DWG NO. DR-PxNGR-09

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION: DR9公叉铆全金黑 8.1

FILE NO.

DRAWING BY


.X ± 0.2
.XX ± 0.1
.XXX ±
AWG

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE