



**Material & Finish**

**SHELL:**

Steel, Nickel Plated

**PIN CONTACT:**

Brass

Gold Flash Plated Over Nickel at Contact Area. Gold Plated Over Nickel at Solder Tail.

**INSULATOR:**

PBT & Glass-fibre reinforced  
UL-94-V0 Black

**BOARD LOCK(Z SHAPE):**

Steel, Tin Plated

**HEXSCREW:**

Steel, Nickel Plated

**CURRENT RATING:**

3 Amp

**CONTACT RESISTANCE:**

20mΩ Max

**DIELECTRIC STRENGTH:**

1000VAC for one minute

**INSULATOR RESISTANCE:**

1000MΩ Min. (at 500VDC)

Dimensions				
Positions	A	B	C	D
09	30.81	24.99	16.33	11.08
15	39.20	33.30	24.70	19.39
25	53.05	47.04	38.40	33.24
37	69.40	63.50	54.80	49.86

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ± 3°

PJECTION

照片框

**ORDER INFORMATION**

DR-SGNJM26-xx-LF  
SERIES | | | LEADFREE  
09~37 WAY  
FEMALE | | | JACK SCREW  
NUT  
GOLD

DESCRIPTION: D-SUB FEMALE R/A TYPE RIVET Z SHAPE, LOCK 5.8 HEX SCREW(M2.6)