



## MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0) BLACK.  
 CONTACT MATERIAL : BRASS.  
 CONTACT FINISH : GOLD OVER NICKEL.  
 SHELL FINISH : STEEL NICKEL PLATED.

## SPECIFICATION:

CURRENT RATING : 5 AMP  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE.  
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.  
 CONTACT RESISTANCE : 15mΩ MAX. 10 SES.  
 OPERATING TEMPERATURE : -55°C ~ +105°C.

SHELL SIZE	Dim A ± 0.20	Dim B ± 0.25	Dim C ± 0.38	Dim D
09 pin	16.33	24.99	30.80	11.08
15 pin	24.66	33.32	39.10	19.39
25 pin	38.38	47.04	53.00	33.24
37 pin	54.84	63.50	69.32	49.86

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

DR-SSLNJ-xx-LF  
 SERIES | | | | | LEADFREE  
 | | | | | 09-37 WAY  
 | | | | | JACKSCREW  
 | | | | | NUT  
 FEMALE | | | | | L TYPE  
 SEMI GOLD

DESCRIPTION: D-SUB CONN.RIGHT ANGLE, FEMALE FOOTPRINT : 8.08mm

煜倫股份有限公司

www.morethanall.com