



MATERIAL-

Insulator: Nylon 9T (Black) ,UL94V-0.
 Contact: Phosphor Bronze or Brass(Standard is Brass)
 Contact Plating: GOLD Plating Over NICKEL In Contact AREA.
 NICKEL Plating In A'SS AREA.
 Shell: Steel ,Nickel Plated.

SPECIFICATION-

Current Rating: 5Amps.
 Insulator Resistance: 1000MegΩ Min ,at 500V DC.
 Contact Resistance: 20milliΩ Max.
 Withstanding Voltage: 1000V AC/minute.
 Max Processing Temperature: 210°C For 30~60 Seconds.
 Operating Temperature: -55°C~ +125°C.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

DR09-PNJ-09-LF

SERIES | LEADFREE
 | 09 WAY
 | JACKSCREW
 | NUT
 | MALE

DESCRIPTION: Slim D-SUB Connector R/A DIP TYPE(2 Prong)