

RECOMMENDED P.C.B LAYOUT
TOLERANCES: ±0.05mm

PARTS DIMENSION TABLE

| parts no. | DIM. a | DIM. b | inner thread |
|-----------|--------|--------|--------------|
| B | 4.8 | 11.8 | 4#40 |
| C | 4.8 | 11.8 | 4#40 |
| D | 5.8 | 12.0 | 4#40 |
| E | 5.8 | 12.0 | 4#40 |

MATERIAL-


Insulator: Nylon 9T (Black), UL94V-0.
 Contact: Phosphor Bronze or Brass(Standard is Brass)
 Contact Plating: GOLD Plating Over NICKEL In Contact Area.
 Tin Plating Over Nickel In Dip Area.
 NICKEL Plating In 4'SS AREA.
 Shell: Steel, Nickel Plated.

SPECIFICATION-

Current Rating: 6Amps.
 Insulator Resistance: 1000MegaΩ Min, at 500V DC.
 Contact Resistance: 20mΩMax.
 Withstanding Voltage: 1000V AC/minute.
 Reflow Processing Temperature & Time: 240°C For 6 Seconds.
 Peak Reflow Processing Temperature & Time: 230°C For 60 Seconds.
 Operating Temperature: -55°C~ +125°C.

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

| | | |
|-----------------------|-------------|----------------|
| RoHS Compliant | | TOLERANCES ARE |
| DRAWING BY | CY | X, ± |
| CHECKED BY | GENIUS | .X ± |
| UNIT / mm | SCALE 1 : 1 | .XXX ± |
| DATE | | ANG ± |
| SIZE A4 | PJECTION | |



ORDER INFORMATION

DR13-SNJ-25-LF
 SERIES | LEADFREE
 | 25 WAY
 | JACKSCREW
 | NUT
 | FEMALE

DESCRIPTION: