



MATERIAL-

Insulator: Nylon 9T (Black) ,UL94V-0.
 Contact: Phosphor Bronze or Brass(Standard is Brass)
 Contact Plating: GOLD Plating Over NICKEL In Contact AREA.
 NICKEL Plating In A'SS AREA.
 Shell: Steel ,Nickel Plated.

SPECIFICATION-

Current Rating: 5Amps.
 Insulator Resistance: 1000MegΩ Min ,at 500V DC.
 Contact Resistance: 20milliΩ Max.
 Withstanding Voltage: 1000V AC/minute.
 Max Processing Temperature: 210°C For 30~60 Seconds.
 Operating Temperature: -55°C~ +125°C.

***P.C.B. LAYOUT**



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

| | |
|-------------------|-------------|
| DRAWING BY CY | |
| CHECKED BY GENIUS | |
| UNIT / mm | SCALE 1 : 1 |
| DATE | |
| SIZE A4 | PJECTION |

TOLERANCES ARE

X.±
 .X±
 .XX±
 .XXX±
 ANG±

照片框

ORDER INFORMATION

DR14-SNJ-09-LF
 SERIES | | | LEADFREE
 | | | 09 WAY
 | | | JACKSCREW
 | | | NUT
 | | | FEMALE

DESCRIPTION: Slim D-SUB Connector R/A DIP TYPE(2 Prong)