



### MATERIALS AND FINISH

SHELL : STEEL MATERIAL, FRONT SHELL NICKEL FINISHED  
 BACK SHELL TIN FINISHED  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS  
 FILLED, UL 94V-0 RATED, WHITE COLOR  
 CONTACT MATERIAL : BRASS  
 CONTACT FINISH : FULL GOLD FLASH  
 RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED  
 JACK SCREWS : BRASS MATERIAL , NICKEL FINISHED

### ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS  
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.  
 TEMPERATURE RATING : -55°C ~ +105°C

Notice:  
 The size has mark is important  
 Need double measure

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X.±

.X±

.XX±

.XXX±

ANG±

PPOJECTION

照片框

### ORDER INFORMATION

DR72-PZ-50-LF  
 SERIES | LEADFREE  
 50 WAY  
 CLIP  
 MALE

DESCRIPTION: 0.283" Footprint D-SUB, Right Angle, Machined Pin