

Recommend P.C.B Layout

1. MATERIALS AND FINISH

SHELL: STEEL MATERIAL, FRONT SHELL TIN FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY


INSULATOR: PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0, BLACK
 CONTACT: COPPER ALLOY, FULL GOLD FLASH

2. SPECIFICATION

CONTACT CURRENT RATING : 5.0 A
 CONTACT RESISTANCE : 10 mΩ MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5GΩ MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

DR72-SZNJ-15-LF

SERIES
 LEADFREE
 15 WAY
 JACKSCREW
 NUT
 CLIP
 FEMALE

DESCRIPTION: D-SUB 90°, FEMALE , L PIECE, 7.2 mm , Machine Pin

煜倫股份有限公司

www.morethanall.com