



RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: ±0.05mm

POSITION	A	B	C
9	16.30	25.00	30.8
15	24.60	33.30	39.2
19	30.00	38.86	44.8
23	35.30	44.30	50.3
25	38.30	47.10	53.1
37	54.80	63.50	69.4

SPECIFICATION

MATERIAL

Insulator: Thermal Plastic UL94V-0

Contacts: Copper Alloy

Shell: Steel

Rivet, Boardlock: Copper Alloy

CONTACT PLATING

Underplate: 50u"~100u" Nickel

Contact Area: 1u"~30u" Selective Gold

ELECTRICAL

Operation Voltage: 250 VAC Max.

Current Rating: 3 Amps Max.

Contact Resistance: 15 mohms Max.

Insulation Resistance: 3000 Mohms Min. @ 500 VDC

Dielectric Withstanding Voltage: 1000 VAC / minute

Temperature Range: -55°C to +105°C

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

DR94-SZJ-xx-LF

SERIES | | | LEADFREE
| | | 09~37 WAY
| | | JACK SCREW
| | | CLIP
| | | FEMALE

DESCRIPTION: