

P.C.B LAYOUT

No. of Contact	A ±0.25 ±.010	B ±0.13 ±.005	C ±0.38 ±.015	D ±0.25 ±.010	E
25	38.38 1.511	47.04 1.852	53.04 2.088	41.28 1.625	33.24 1.310

### MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS  
 FILLED, UL 94V-0 RATED, WHITE COLOR  
 CONTACT MATERIAL : BRASS  
 CONTACT FINISH : FULL GOLD FLASH

### ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS  
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.  
 TEMPERATURE RATING : -55°C ~ +150°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1


.XXX±

DATE

ANG±

SIZE A4

PJECTION



### ORDER INFORMATION

DR941-SZJ-25-LF

SERIES | LEADFREE  
 | 25 WAY  
 | JACKSCRW  
 | CLIP  
 | FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: D-sub Machined Pin .37" Footprint