



PCB LAYOUT

**MATERIALS AND FINISH**

SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED  
 BACK SHELL TIN FINISHED  
 DIMPLES ON PLUG ONLY  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, BLACK COLOR  
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

**ELECTRICAL CHARACTERISTICS**

CONTACT CURRENT RATING : 7.5 AMPS  
 CONTACT RESISTANCE : 10 mΩ MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X.±  
 .X±  
 .XX±  
 .XXX±  
 ANG±

照片框

ORDER INFORMATION

DR941-SZNJ-25-LF

SERIES  
 LEADFREE  
 25 WAY  
 JACKSCREW  
 NUT  
 CLIP  
 FEMALE

DESCRIPTION: