



RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(M)

NOTES

- MATERIAL:**
Housing:PBT, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Boardlock:Copper Alloy.
Bracket:Zinc Alloy.
Screw:Copper Alloy.
- FINISH:**
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Area.
Shell:Nickel Plated.
Boardlock:Tin Plated.
Bracket:Nickel Plated.
Screw:Nickel Plated.
- This Product is LEAD-FREE & RoHS Compliance Product.

SPECIFICATIONS

- D-SUB
 - Voltage: 250 VAC(RMS) Max.
 - Current Rating: 3 Ampere per Contact
 - Contact Resistance: 25 Milliohms Max.
 - Insulation Resistance: 5000 Megohms Min.
 - Dielectric Withstanding Voltage: 1000V AC(RMS)
 - Total Mating Force: 9.7 Kgf Max.
 - Total Unmating Force: 1.4 Kgf Min.
 - Operating Temperature: -55°C to +85°C



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±
.X ±
.XX ± 0.25
.XXX ± 0.13
ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

DRB1-AN19J-2626-LF

SERIES | | | LEADFREE
26 TO 26 WAY
JACKSCRW
SPACING 19.05mm
NUT
FEMALE TO MALE

DESCRIPTION: D-SUB HIGH DENSITY CONNECTOR 0.350"(8.89) FOOTPRINT, DUAL PORT