



P.C.B LAYOUT

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, NICKEL FINISHED
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
 CONTACT MATERIAL : BRASS
 CONTACT FINISH : SELECTIVE GOLD FLASH
 GROUNDING BRACKET : ZINC ALLOY, ZINC PLATED
 RIVETED INSERT : BRASS MATERIAL, NICKEL FINISHED
 JACK SCREWS : BRASS MATERIAL, NICKEL FINISHED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

ROHS Compliance

DRB1-FN19-1515C-LF
 LEADFREE

RoHS Compliant



PART NO. DRB1-FN19-1515C

DWG NO. DRB1-FN19-1515C

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

D-sub Stack Connector,
 R A, 15S 15S, 0.75"

煜倫股份有限公司

FILE NO.

DRAWING BY

.X ± 0.2
 .XX ± 0.1
 .XXX ±
 AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION