



RECOMMENDED P.C.B LAYOUT

NOTES

- MATERIAL:**  
 Housing:PBT, UL 94V-0, Color:Black.  
 Terminal:Copper Alloy.  
 Shell:SPCC.  
 Boardlock:Copper Alloy.  
 Rivet:Copper Alloy.  
 Screw:Copper Alloy.
- FINISH:**  
 Terminal:Gold Plated over Nickel at Contact Area.  
 Tin Plated over Nickel at Solder Ared.  
 Shell:Nickel Plated.  
 Boardlock:Tin Plated.  
 Rivet:Nickel Plated.  
 Screw:Nickel Plated.
- This Product is RoHs Compliance Product.

SPECIFICATIONS

- D-SUB
  - Voltage: 250 VAC(RMS) Max.
  - Current Rating: 3 Ampere per Contact
  - Contact Resistance: 25 Milliohms Max.
  - Insulation Resistance: 5000 Megohms Min.
  - Dielectric Withstanding Voltage: 1000V AC(RMS)
  - Total Mating Force: 4.0 Kgf Max.
  - Total Unmating Force: 1.0 Kgf Min.
  - Operating Temperature: -55°C to +85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
 X, ±  
 .XX ± 0.25  
 .XXX ± 0.13  
 ANG ± 2°

P PROJECTION

照片框

ORDER INFORMATION

DRF-PSNJ-09-LF  
 SERIES | | | | LEADFREE  
 | | | | 09 WAY  
 | | | | JACKSCRW  
 | | | | NUT  
 | | | | SEMI GOLD  
 | | | | MALE

DESCRIPTION: D-SUB 0.318"(8.08mm) FOOTPRING, RIGHT ANGLE, WITH FERRITE