



Positions	A	B	C
09	16.35	24.99	30.61
15	24.66	33.32	39.14
25	38.38	47.04	53.04
37	54.84	63.50	69.32

Material & Finish

SHELL:

Steel
Zinc plated, Tin plated
or Nickel plated steel

PIN CONTACT:

Phosphor bronze or brass

INSULATOR:

PBT & Glass-fibre reinforced
UL-94-V0

NUMBER OF CONTACT:

9,15,25,37

CURRENT RATING:

3 Amp

DIELECTRIC STRENGTH:

AC 1000V Min. (for one minute)

INSULATOR RESISTANCE:

500MΩ Min. (at 500V DC)

CONTACT RESISTANCE

15mΩ Max. mated

TEMPERATURE:

-55° C to +105° C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

DRL-SGNM-xx-LF
SERIES | | | LEADFREE
| | | 09-37WAY
| | | MIDDLE CLIP
| | | NUT
| | | GOLD
| | | FEMALE

DESCRIPTION: D-SUB P.C.B. RIGHT ANGLE FEMALE 13.84mm RIVET Z SHAPE (中耳)