



**SPECIFICATION**

**MATERIAL**

Insulator: Thermal Plastic UL94V-0

Contacts: Copper Alloy

Shell: Steel

Rivet, Boardlock: Copper Alloy

**CONTACT PLATING**

Underplate: 50u" Nickel

Contact Area: 1u"~50u" Selective Gold

Solder Tails Area: 100u" Tin/Lead (Brighten Tin) or

100u" Tin/Lead Free (Brighten Tin/Matte Tin)

**ELECTRICAL**

Operation Voltage: 250 VAC Max.

Current Rating: 3 Amps Max.

Contact Resistance: 15 mohms Max.

Insulation Resistance: 3000 Mohms Min @ 500 VDC

Dielectric Withstanding Voltage: 1000 VAC / Minute

Operating Temperature: -55°C TO +105°C

DS-PGB-09-LF

LEADFREE

RoHS Compliant



PART NO. DS-PGB-09

DWG NO. DS-PGB-09

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

AWG

DESCRIPTION:

D-SUB SOLDER MALE (9 POSITION)

AREA

REVISIONS

HK

DATE

煜倫股份有限公司