



Positions	A	B	C	D
09	16.92	24.99	30.81	19.28
15	25.25	33.32	39.14	27.65
25	38.96	47.04	53.04	41.30
37	55.42	63.50	69.32	57.44

## Material & Finish

### SHELL:

Steel  
Zinc plated, Tin plated  
or Nickel plated steel

### PIN CONTACT:

Brass, Selective Gold plated 1~3u" over  
Nickel plated 50u" Min.

### INSULATOR:

PBT & Glass-fibre reinforced  
UL-94-V0

### NUMBER OF CONTACT:

9,15,25,37

### CURRENT RATING:

5 Amp

### DIELECTRIC STRENGTH:

500V for one minute

### INSULATOR RESISTANCE:

1000MΩ Min. (at 500V DC)

### TEMPERATURE:

-55° C to +105° C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±  
.X ± 0.30  
.XX ± 0.25  
.XXX ± 0.15  
ANG ± 3°

照片框

ORDER INFORMATION

DS-PSBK-xx-LF  
SERIES | LEADFREE  
09~37WAY  
BLACK  
SEMI GOLD  
MALE

DESCRIPTION: D-SUB SOLDER TYPE MALE (一體)(9-37)