




Note:

1.Material:

1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0

1.2 Contact: Copper alloy,t=0.20mm

1.3 Shell: Spcc,t=0.30mm

2.Specification:

2.1 Current rating: 1 A Max.

2.2 Dielectric withstanding

voltage: 750 V(ac) for 1 min.

2.3 Contact resistance: 30 mΩ Max.

2.4 Insulation resistance: 1000 MΩ Min.

2.5 Total mating force: 7.0 Kgf Max.

2.6 Total unmating force: 1.5 Kgf Min.

2.7 Temperature range: -55°C~85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10	J±0.25	K±0.25
DS-SSN-09	30.81	24.99	16.33	7.9	15.0		12.55	2.77	2.84		
DS-SSN-15	39.25	33.32	24.66	7.9	15.0		12.55	2.77	2.84		
DS-SSN-25	53.04	47.04	38.38	7.9	15.0		12.55	2.77	2.84		
DS-SSN-37	69.50	63.50	54.84	7.9	15.0		12.55	2.77	2.84		

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION



ORDER INFORMATION

DS-SSN-xx-LF
SERIES
LEADFREE
09~37 WAY
NUT
SEMI GOLD
FEMALE

DESCRIPTION: D-SUB SOLDER FEMALE 鍍後型 (通孔)