



Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Mating force: 5.5 Kgf Max.
6. Unmating force: 1.7 Kgf Min.
7. Temperature range: -55°C~+105°C

7	3B Nut	2	Brass	H4.75*5.50	80~120u*Nickel Plated
6	3B Nut	2	Brass	H4.75*4.75	80~120u*Nickel Plated
5	8.0 Nut	2	Brass	H4.75*8.0	80~120u*Nickel Plated
4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Cu:40u*min. 80~120u*Tin Plated
3	Front-shell	1	Cold Rolled Steel	T=0.40mm	Cu:40u*min. 80~120u*Nickel Plated
2	Contact	9	Brass	T=0.20mm	Contact area:0.8~1.2u*Gold Plated over 40u*Nickel min. Solder area:80~120u*Tin Plated over 40u*Nickel min.
1	Housing	2	P.B.T	UL 94-V0	Black/Blue/White
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

DS-SSNM3-09-LF
SERIES | | | | | LEADFREE
| | | | | 09 WAY
| | | | | M3
| | | | | NUT
| | | | | SEMI GOLD
| | | | | FEMALE

DESCRIPTION: HDD RIGHT ANGLE P.C.B TYPE 26PIN(M) 鉚鎖 NUT