




Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Copper alloy,t=0.20mm.
- 1.3 Shell: Cold rolled steel,t=0.40mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total mating force: 8.0 Kgf Max.
- 2.6 Total unmating force: 1.5 Kgf Min.
- 2.7 Temperature range: -55°C~+105°C

4	Back-shell	1	Cold Rolled Steel	T=040mm	Tin Plated
3	Front-shell	1	Cold Rolled Steel	T=0.40mm	Nickel Plated
2	Contact	9~37	Copper alloy	T=0.20mm	Gold Plated
1	Housing	2	P.B.T	UL 94-V0	Blue / Blkck
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10	J±0.25	K±0.25
DS-SSxx-09	30.81	24.99	16.33	7.9	15.0		12.55	2.77	2.84		
DS-SSxx-15	39.25	33.32	24.66	7.9	15.0		12.55	2.77	2.84		
DS-SSxx-25	53.04	47.04	38.38	7.9	15.0		12.55	2.77	2.84		
DS-SSxx-37	69.50	63.50	54.84	7.9	15.0		12.55	2.77	2.84		

照片框

RoHS Compliant			TOLERANCES ARE	
 煜倫股份有限公司 www.morethanall.com	DRAWING BY CY		X. ±	
	CHECKED BY GENIUS		.X ±	
	UNIT / mm	SCALE 1 : 1	.XX ±	
	DATE		.XXX ±	
SIZE A4			ANG ±	
PPOJECTION				

ORDER INFORMATION	
DS-SSxx-xx-LF	
SERIES	LEADFREE
	09~37WAY
	BK:BLACK
	WH:WHITE
	SOLDER
	FEMALE
DESCRIPTION: D-SUB SOLDER (F)	