



MATERIAL:

INSULATOR : PBT%30GLASS FIBER (UL 94V-0).
 CONTACT MATERIAL : BRASS.
 CONTACT FINISH : GOLD OVER NICKEL.
 SHELL FINISH : STEEL, TIN PLATED OR NICKEL, ZINC.

SPECIFICATION:

CURRENT RATING : 5 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE.
 INSULATION RESISTANCE : ~~1000MΩ~~ AT 500V DC.
 CONTACT RESISTANCE W: ~~15mΩ~~ 10 SES.
 OPERATING TEMPERATURE $^{\circ}\text{C}$ -55+105

NO.OF CONTACT	A ± 0.20	B ± 0.25	C ± 0.38	D ± 0.20
9P	16.92	24.99	30.80	19.14
15P	25.25	33.32	39.10	27.47
25P	38.96	47.04	53.00	41.19
37P	55.42	63.50	69.32	57.65

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫有限公司

PART NO. DSF-P-XX

DWG NO. DSF-P-XX

FILE NO. 02FA-XX1XXA-

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 AWG

DESCRIPTION:

D-SUB SOLDER MALE WITH FILTER FOR EMI STAMPED CONTACTS

AREA

REVISIONS

HK

DATE