



MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0).
 CONTACT MATERIAL : BRASS.
 CONTACT FINISH : GOLD OVER NICKEL.
 SHELL FINISH : STEEL, TIN PLATED OR NICKEL, ZINC.

SPECIFICATION:

CURRENT RATING : 5 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 15mΩ MAX. 10 SES.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

NO.OF CONTACTS	A ± 0.20	B ± 0.25	C ± 0.38	D ± 0.20
9S	16.33	24.99	30.80	19.14
15S	24.66	33.32	39.10	27.47
25S	38.38	47.04	53.00	41.19
37S	54.84	63.50	69.32	57.65

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫有限公司

PART NO. DSF-S-XX

DWG NO. DSF-S-XX

FILE NO. 02FA-XX0XXA-

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 AWG

DESCRIP TION:

D-SUB SOLDER FEMALE WITH FILTER FOR EMI
 STAMPED CONTACTS

AREA

REVISIONS

HK

DATE