



NOTE:

MATERIALS

- 1.HOUSING : PBT+25%
- 2.CONTACT : BRASS, GOLD/TIN PALTED
- 3.FRONT SHIELD : SPCC, NICKEL PALTED
- 4.BACK SHIELD : SPCC, TIN PLATED

SPECIFICATION:

- 1.CURRENT RATING: 1.5 AMP. MAX
- 2.DIELECTRIC WITHSTANDING VOLTAGE:
500V AC R.M.S. FOR ONE MINUTE
- 3.INSULATION RESISTANCE: 1000M OHMS MIN.AT 500V DC
- 4.CONCACT RESISTANCE: 20m OHMS MAX
- 5.OPERATINC TEMPERATURE: 0°C TO +85°C
- 6.MAX. PROCESSING TEMPERATURE:
230°C FOR 30~60 SECONDS(HI.-TEMP.PLASTIC)
- 7.THE 14PIN HIGHEST SHORT 0.76m/m OTHER PIN

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X.±

.X±

.XX±

.XXX±

ANG±

PJECTION

照片框

ORDER INFORMATION

DVI-PS-12+5-LF
SERIES | LEADFREE
12+5 PIN
SOLDER
MALE

DESCRIPTION: DVI 12+5公(BC) 半金黑