



MATERIALS

- 1.HOUSING : PBT+25%
- 2.TERMINAL : BRASS GOLD AND TIN PALTED
- 3.FRONT SHIELD : SPCC NICKEL PALTED
- 4.BACK SHIELD : SPCC TIN PLATING PLATED

SPECIFICATION:

- 1.CURRENT RATING:1.5AMP. MAX
- 2.DIELECTRIC WITHSTANDING VOLTAGE 500V AC R.M.S. FOR ONE MINUTE
- 3.INSULATION RESISTANCE:1000M OHMS MIN.AT 500V DC
- 4.CONCACT RESISTANCE:20M OHMS MAX
- 5.OPERATINC TEMPERATURE:0°C TO +85°C
- 6.MAX. PROCESSING TEMPERATURE: 230°C FOR 30~60 SECONDS(HI.-TEMP.PLASTIC)

PART NO.	PLATING	COLOR
DVI-PS-18+1	GOLD(3u') OR TIN PLATED	WHITE

NOTE:

THE 14PIN HIGHEST SHORT 0.76m/m OTHER PIN

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

DVI-PS-18+1-LF
SERIES | LEADFREE
18+1 PIN
SOLDER
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DVI 18+1公半金白色