



NOTE:

ELECTRICAL

RATED:1.5A 40V (AC)

CONTACT RESISTANCE:30mΩ MAXIMUM.

INSULATION RESISTANCE:1000MΩ MINIMUM.

DIELECTRIC WITHSTANDING VOLTAGE:500V

MECHANICAL

MATING FORCE:4.5KG MAX.

UNMATING FORCE:4KG MAX.

UNMATING FORCE:1KG MIN.

MATERIAL:

PLASTIC CORE:PBT 加纖, BLACK/WHITE

SHELL: SPCC T=前線後錫

TERMINAL:C2680-H 前端電鍍金(0.8U"min)尾端鍍錫80u"min

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

DVI-PS-24+1-LF  
SERIES | LEADFREE  
24+1 WAY  
SOLDER  
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DVI 24+1 公頭焊線式