


Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Temperature range: -55°C~+105°C

5	Back-shell	1	Cold rolled steel	T=0.40mm	Cu:40u"min. 80u"min Tin Plated
4	Front-shell	1	Cold rolled steel	T=0.40mm	Cu:40u"min. 80u"min Nickel Plated
3	Grounding strip	1	Brass	T=0.40mm	Contact area:0.8u"min Gold Platedover 40u"Nickel min. Solder area:80u"min Tin Plated over 40u"Nickel min.
2	Contact	24	Brass	T=0.45mm	Contact area:0.8u"min Gold Plated over 40u"Nickel min. Solder area:80u"min Tin Plated over 40u"Nickel min.
1	Housing	1	PBT	UL 94-V0	White/Black
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

DVI-PSxx-24+1-LF
SERIES | LEADFREE
24+1WAY
BLANK:WHITE
BK:BLACK
SOLDER
MALE

DESCRIPTION: DVI(24+1)PIN(M)焊線式(有隔欄)