

PCB LAYOUT (BOTTOM VIEW) TOLARANCE: ±0.05

NOTES:

1. MATERIALS:  
INSULATOR: GLASS FIBER REINFORCED THERMOPLASTIC LCP UL94V-0.  
CONTACT: PHOSPHOR BRONZE, GOLD FLASH ON CONTACT, TIN PLATED ON TAIL 100 $\mu$ ², OVER NICKEL PLATED 50 $\mu$ ².  
SHELL: ZINC ALLOY NICKEL PLATED.
2. ELECTRICAL:  
INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM  
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC  
VOLTAGE RATING: 40 VOLTS AC(RMS) MAXIMUM  
CURRENT RATING: 3.0 AMPS PER CIRCUIT  
CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM
3. MECHANICAL PERFORMANCE:  
INSERTION FORCES: 4.5kgf MAXIMUM  
WITHDRAWAL FORCES: 1kgf MINIMUM, 4kgf MAXIMUM  
DURABILITY: 100 CYCLES MINIMUM
4. ENVIRONMENTAL:  
TEMPERATURE RANGE: -20°C TO +85°C

DVI-SDZ-24+5-LF  
LEADFREE

RoHS Compliant

**MORE THAN ALL**  
CONNECTORS  
ASSEMBLIES

PART NO. DVI-SDZ-24+5

DWG NO. DVI-SDZ-24+5

CHECKED BY CY

TOLERANCES ARE

FILE NO.

DRAWING BY

.X ± 0.2  
.XX ± 0.1  
.XXX ±  
AWG


DESCRIPTION: DVI 24+5 180度母座BC

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE