



PCB LAYOUT (BOTTOM VIEW)

- NOTES:
- 1.MATERIALS:
 - INSULATOR: LCP UL94V-0.
 - CONTACT: PHOSPHOR BRONZE, GOLD FLASH ON CONTACT, TIN PLATED ON TAIL 100u", OVER NICKEL PLATED 50u".
 - SHELL: IRON, NICKEL PLATED.
 - GROUNDING CLIP: BRASS, TIN PLATED.
 - RIVET: BRASS, NICKEL PLATED.
 - 2.ELECTRICAL:
 - INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM
 - DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC R.M.S
 - VOLTAGE RATING: 40 VOLTS AC(RMS) CONTINUOUS MAXIMUM
 - CURRENT RATING: 1.5A MINIMUM, 3.0A MAXIMUM
 - CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM
 - 3.ENVIRONMENTAL:
 - TEMPERRATURE RANGE: -55°C TO +125°C



PART NO. DVI-SDZH-24+5

DWG NO. DVI-SDZH-24+5

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

- .X ± 0.3
- .XX ±
- .XXX ±
- AWG

DESCRIP TION: DVI 24+1 180度母座貝桔色

AREA	REVISIONS	HK	DATE

煜倫股份有限公司