



PCB LAYOUT (BOTTOM VIEW) TOLERANCE: ±0.05

NOTES:

1.MATERIALS:

INSULATOR: GLASS FIBER REINFORCED THERMOPLASTIC LCP UL94V-0.
 CONTACT: PHOSPHOR BRONZE, GOLD FLASH ON CONTACT, TIN PLATED ON TAIL 100µ", OVER NICKEL PLATED 50µ".
 SHELL: ZINC ALLOY, NICKEL PLATED.
 BOARD/DOCK: BRASS, TIN PLATED.
 RIVET: BRASS, NICKEL PLATED.

2.ELECTRICAL:

INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC
 VOLTAGE RATING: 40 VOLTS AC(RMS) MAXIMUM
 CURRENT RATING: 3.0 AMPS PER CIRCUIT
 CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM

3.MECHANICAL PERFORMANCE:

MATING FORCES: 4.5kgf MAXIMUM
 UNMATING FORCES: 1kgf MINIMUM, 4kgf MAXIMUM
 DURABILITY: 100 CYCLES MINIMUM

4.ENVIRONMENTAL:

TEMPERATURE RANGE: -20°C TO +85°C

備注:重點尺寸標示 [XX]

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XXX±

DATE

ANG±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

DVI-SRN-18+5-LF
 SERIES | LEADFREE
 | 18+5 WAY
 | NUT
 | DIP 90°
 FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DVI18+5母(BC) 半金貝吉色 無后鐵殼