



- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 5MΩ

DVIHD-EMBK-2915-LF
LEADFREE
RoHS Compliant

COMPONENTS	DESCRIPTION	Q' / Y
1 DVIA29M	DVI-Analog 24P+4P+Key Male Connector Insulator: High Temperature Plastic UL-94V-0 Contact: Brass Shell: Steel With Tin Plated 150μ" Over Contact Plating: Gold On Contact Area And Tin/LEAD On Solder Cup All With Nickel Underplating	1
2 Jack Screw	UNC #4-40 Nickel Plated	2
3 Hood	P.V.C Molded Color: Black Inner Molded With Copper Foil Shielded	1
4 Screw Lock	UNC #4-40 Nickel Plated	2
5 HD15F	D-SUB High Density 15P Female Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Brass G/F Gold Plated	1

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. DVIHD-EMBK-2915

DWG NO. DVIHD-EMBK-2915

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

焯倫股份有限公司