

WIRE LIST:

P1	P2
C1	1
C2	2
C3	3
15	5
	10
C5	6
	7
14	8
16	9
7	12
C4	13
8	14
6	15
SHELL	SHELL

MOLDING 45P PVC COLOR

RoHS Compliant

PART NO.	PVC COLOR
DVIHD-EMTW-1715	TRANSPARENCE WHITE
DVIHD-EMTB-1715	TRANSPARENCE BLUE
DVIHD-EMBG-1715	BEIEG

NOTE:

- HOOK UP WIRE :UL1007 28AWG*1C TINNED COPPER WIRE,INSULATION: PVC OD=1.20±0.1mm.
- CONNECTOR:
P1.DVI 12+5 MALE CONNECTOR,CONTACT GOLD FLASH, INSULATOR WHITE.TIN PLATED SHELL WITH CAN SHIELD
P2.HDD 15P FEMALE CONNECTOR.CONTACT GOLD FLASH. INSULATOR BLACK.NICKEL PLATED SHELL
- ELECTRONIC TEST CONDITION:
3.1.100%OPEN-SHORT&MIS WIRE TEST.
3.2.CONDUCTIVE RESISTANCE:1Ω MAX.
3.3.INSULATION RESISTANDE:2MΩ MIN.DC300V 10ms.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

DVIHD-EMxx-1715-LF

SERIES

LEADFREE

17 TO 15 WAY

TW:TRANSPARENCE WHITE

TB:TRANSPARENCE BLUE

BG:BEIEG

MOLDING

MALE TO FEMALE

DESCRIPTION: DVI12+5/HDD15F ADAPTER