



WIRE LIST:

P1	P2
C1	1
C2	2
C3	3
15	5
	10
C5	6
	7
14	8
16	9
7	12
C4	13
8	14
6	15
SHELL	SHELL

PE BAG	PE BAG:60*90*0.06mm
PVC	MOLDED 45 PVC
SCREW	SCREW #4-40UNC,Ø5.8*23mm NICKEL PLATED
CONN.	HDD 15P FEMALE CONNECTOR SOLDER TYPE CONTACT GOLD FLASH.INSULATOR BLACK.NICKEL PLATED FRONT SHELL PLATED SHELL TIN PLATED BACK SHELL
CONN.	DVI 24+5 MALE CONNECTOR SOLDER TYPE CONTACT GOLD FLASH INSULATOR WHITE.FRONT NICKEL PLATED BACK TIN PLATED BACK SHELL
CABLE	HOOK UP WIRE:UL1061 28AWG*1C TINNED COPPER WIRE, INSULATION:YELLOW PVC OD=0.9±0.1mm.L=22±1mm.
CABLE	HOOK UP WIRE:UL1061 28AWG*1C TINNED COPPER WIRE, INSULATION:BLACK PVC OD=0.9±0.1mm.L=17±1mm.
NAME	DESCRIPTION

NOTE:

1. ALL MATERIALS/PROCESSES ARE ROHS COMPLIANT.

ELECTRONIC TEST CONDITION:
100% OPEN SHORT & MISWIRE TEST.
CONDUCTIVE RESISTANCE:3Ω /MAX
INSULATION RESISTANCE:20MΩ /MIN.AT DC 300V

DVIHD-EMxx-2915-LF
LEADFREE
BK:BLACK
BG:BEIGE
RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. DVIHD-EMxx-2915

DWG NO. DVIHD-EMxx-2915

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

FILE NO.

DRAWING BY

.X ± 0.2
.XX ±
.XXX ±
AWG

AREA

REVISIONS

HK

DATE

焯倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

