



**PHYSICAL CHARACTERISTICS**

INSULATOR MATERIAL : THERMOPLASTIC UL 94V-0,  
COLOR : BLACK

CONTACT MATERIAL : BRASS (FEMALE SIGNAL CONTACT)  
BRASS (PIN SIGNAL CONTACT)  
BRASS (POWERS CONTACT)

SHELLS : STEEL BRIGHT TIN

JACKSCREWS : BRASS, PLATE WITH NICKEL.

PUSH FASTENERS : BERYLLIUM COPPER WITH TIN PLATE.

MOUNTING BRACKETS : IRON, PLATE WITH TIN.

**ELECTRICAL CHARACTERISTICS**

HIGH POWER CONTACT CURRENT RATING : 10 , 20 , 30 , 40 AMPS

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC FOR 1 MINUTE  
INSULATION RESISTANCE : 5000 MEGAOHMS MIN.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

**ORDER INFORMATION**

DWR-S10ZJ-09W4-LF  
SERIES | | | | LEADFREE  
| | | | JACK SCREW  
| | | | CLIP  
| | | | 10 AMP  
| | | | FEMALE

DESCRIPTION: D-SUB 9W4 10amp JACK L LATCH+BOARD LOCK

煜倫股份有限公司

www.morethanall.com