



**MATERIALS AND FINISH**  
 SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED  
 BACK SHELL TIN FINISHED  
 DIMPLES ON PLUG ONLY  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, BLACK COLOR  
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

**ELECTRICAL CHARACTERISTICS**  
 SIGNAL CONTACT CURRENT RATING : 7.5 AMPS  
 SIGNAL CONTACT RESISTANCE : 2.7 mΩ MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC FOR 1 MINUTE  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C

DWS-P-13W6-LF  
 LEADFREE

RoHS Compliant



煜倫股份有限公司

PART NO. DWS-P-13W6		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:			
DWG NO. DWS-P-13W6		DRAWING BY						
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1							