



MATERIALS AND FINISH
 SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,
 UL 94V-0 RATED, BLACK COLOR
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

ELECTRICAL CHARACTERISTICS
 SIGNAL CONTACT CURRENT RATING : 7.5 AMPS
 SIGNAL CONTACT RESISTANCE : 2.7 mΩ MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC FOR 1 MINUTE
 INSULATION RESISTANCE : 10⁷MΩ MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

DWS-S-36W4-LF
 LEADFREE
 RoHS Compliant

MORE THAN ALL
 CONNECTORS
 ASSEMBLIES

PART NO. DWS-S-36W4	CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:	AREA	REVISIONS	HK	DATE
	DWG NO. DWS-S-36W4	DRAWING BY						
FILE NO.	UNIT / mm	SCALE 1:1	PROJECTION					

煜倫股份有限公司