



MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
 CONNECTOR INSULATOR : PBT THERMOPLASTIC,
 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
 HIGH POWER CONTACT MATERIAL: BRASS, 15u" GOLD PLATED

ELECTRICAL CHARACTERISTICS

HIGH POWER CONTACT CURRENT RATING : 10 OR 20 OR 40 AMPS
 HIGH POWER CONTACT RESISTANCE : 2.7 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE :
 1000 V AC FOR 1 MINUTE
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

PART NO.	Dimension	current rating
DWS-S10-08W8	Ø1.70	10A
DWS-S20-08W8	Ø2.80	20A
DWS-S40-08W8	Ø3.75	40A

MORETHANALL
 CONNECTORS
 ASSEMBLIES

焯倫有限公司

PART NO. DWS-Sxx-08W8

DWG NO. DWS-Sxx-08W8

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X ±0.3
 .XX
 .XXX
 AWG

DESCRIP TION:	D-SUB CONNECTOR (Power Contact Solder Type)(08W)			
	AREA	REVISIONS	HK	DATE