



PIN ASSIGNMENT

P1	P2
A1 — 20AWG	A1
A2 — 20AWG	A2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
S — DRAIN&BRAID	S

NO.	DESCRIPTION	Q'TY	UNIT
*	TIE-A/GRAY	100*1	MM
*	CARTON:46*30*20CM	A/R	PCS
*	PE BAG:30*28*0.08MM	A/R	PCS
*	PE BAG:6*8*0.06MM	1	PCS
6	SCREW E31.5 BK10	4	PCS
5	PVC-BK10/50P (UL94V-0)	64	G
4	PE-5321	11.2	G
3	SOLDER TYPE MALE 20A POWER PIN	4	PCS
2	D-SUB 17W2 MALE BLACK POWER PIN	2	PCS
1	CABLE UL2464 #28*15C+#20*2C+A+D, BK10 OD6.5	1.5	M
NO.	DESCRIPTION	Q'TY	UNIT

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±  
.X ± 0.50  
.XX ±  
.XXX ±  
ANG ± 3°

照片框

ORDER INFORMATION

DWX2-17W22028-M1M5-LF

SERIES

17W2

20/28 AWG

1500mm

LEADFREE

MALE TO EMAL

DESCRIPTION: CABLE D-SUB 17W2 MALE / D-SUB 17W2 MALE L=1.5M