



PCB LAYOUT

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
 DIMPLES ON PLUG ONLY
 CONNECTOR INSULATOR : PBT THERMOPLASTIC,
 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
 COAXIAL INSULATOR : TEFLON UL 94V-0 WHITE COLOR
 SIGNAL CONTACT MATERIAL: BRASS, FULL GOLD FLASH
 COAXIAL CONTACT MATERIAL: BRASS, 15u" GOLD PLATED

ELECTRICAL CHARACTERISTICS

SIGNAL CONTACT CURRENT RATING : 3.0 AMPS
 SIGNAL CONTACT RESISTANCE : 10 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE :
 1000 V AC FOR 1 MINUTE
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +125°C
 COAXIAL CONTACT IMPEDANCE: 75 OHMS



A	PART NO. DXS-P75-21W1		CHECKED BY CY	TOLERANCES ARE .X±0.2 .XX± .XXX± AWG	DESCRIP TION: D-SUB CONNECTOR (Coaxial Contact Solder Type)	AREA	REVISIONS	HK	DATE
	DWG NO. DXS-P75-21W1								
B	FILE NO.		PROJECTION						
	UNIT / mm	SCALE 1:1							

煜倫股份有限公司